

exciters/all-in-one transmitters

- > **easy maintenance exciter series**
- > **All-in-One transmitter series**
- > **All-in-One high fidelity series**

**TEX30 LCD/S TEX150 LCD/S
TEX50 LCD/S TEX300LCD
TEX100LCD/S**



TEX300LCD front view

Features

- > **PRIMARY APPLICATION:** high quality at a very attractive price. Ideal for use as exciters in compact and modular system.
- > **HARDWARE FEATURES:** compact, non-deformable and light thanks to the stainless steel chassis, in 2 rack units only.
- > **USER-FRIENDLY FEATURES:** universal 80-260 V multi-voltage power supply enables operation without preselect voltage. Four pushbuttons for user/device interaction and software that offers a simple, intuitive interface.
- > **RELIABILITY/CONTINUITY:** APC (Automatic Power Control) and Foldback protection ensure reliable operation under any operating conditions.
- > **AUDIO PERFORMANCE:** low distortion and intermodulation values and a high noise/signal ratio.
- > **OPERATING EFFICIENCY:** incorporate a PFC (Power Factor Corrector) power supply, that provides the utmost efficiency for enhanced energy saving and environmental protection, which ensure high efficiency across the bandwidth.
- > **EASE OF MAINTENANCE:** advanced module engineering ensures extreme of access and simple maintenance.
- > **INTERFACE CONTROL:** total control thanks to microprocessor easily programmed from menu with all key parameters displayed on LCD.
- > **INPUT/OUTPUT INTERFACE:** built-in high-performance stereo coder, L&R analogue audio inputs, Mono inputs, MPX composite signal and auxiliary inputs for SCA / RDS signals.
- > **RDS APPLICATION:** built-in RDS encoder with UECP standard functions (option).
- > **REMOTE CONTROL:** built-in telemetry system via GSM modem, battery and battery charger or via WEB or via SNMP (option).
- > **REGULATORY COMPLIANCE:** state-of-the-art technology in full compliance with EC, FCC and CCIR standards.

Caratteristiche

- > **PRIMARY APPLICATION:** alta qualità ad un prezzo estremamente contenuto, ideali come eccitatori in sistemi compatti e modulari.
- > **HARDWARE FEATURES:** compatti, indeformabili e leggeri perché realizzati in chassis di acciaio inox, in sole 2 unità rack.
- > **USER-FRIENDLY FEATURES:** utilizzabili a diverse tensioni di rete da 80 V a 260 V senza necessità di preselezione. Quattro tasti a pressione per l'interazione fra l'utente e l'apparato unita ad un software intuitivo e semplificato.
- > **RELIABILITY/CONTINUITY:** elevata continuità di esercizio garantita in qualsiasi condizione di lavoro attraverso un controllo automatico APC ed una protezione di Foldback.
- > **AUDIO PERFORMANCE:** bassi valori di distorsione, di intermodulazione e alto rapporto segnale rumore.
- > **OPERATING EFFICIENCY:** per un risparmio di risorse energetiche e ambientali, utilizzano un alimentatore PFC (Power Factor Corrector) che garantisce rendimenti elevati su tutta la banda.
- > **EASE OF MAINTENANCE:** estrema accessibilità e semplicità di manutenzione grazie ad una avanzata ingegnerizzazione modulare dell'apparato.
- > **INTERFACE CONTROL:** controllo completo basato su microprocessore e da menu con lettura su display LCD di tutti i parametri principali.
- > **INPUT/OUTPUT INTERFACE:** stereo coder integrato ad elevate prestazioni, ingressi audio analogici L&R, Mono e segnale composto MPX ed ausiliari per segnali SCA / RDS.
- > **RDS APPLICATION:** encoder RDS integrato UECP standard (versione vendibile opzionalmente).
- > **REMOTE CONTROL:** sistema di telemetria integrato via modem GSM, batteria e caricabatteria o via WEB o via SNMP (versione vendibile opzionalmente).
- > **REGULATORY COMPLIANCE:** tecnologia moderna e pienamente rispondente alle normative EC, FCC ed CCIR.

UK

35, Brompton Square, Knightsbridge,
London, SW3 2AE, UK

+44 (0) 7421 388 981

transmitterman

Cyprus

Box 52748, Christaki Kranou 11,
Germasogeia, Limassol 4041, CYPRUS

+357 97 869349

transmitterman

exciters/all-in-one transmitters

BROADCAST
EQUIPMENT

(Oirt, JPN &
China Band
others
on request)

Technical specifications

Parameter	TEX30LCD	TEX50LCD	TEX100LCD	TEX150LCD	TEX300LCD
GENERALS					
Frequency range	FCC - CCIR - OIRT - JPN - CHN				
Rated output power	30 W	50 W	100 W	150 W	300 W
Modulation type	Direct carrier frequency				
Operational Mode	Mono, Stereo, Multiplex				
Environmental working conditions	-10 °C to + 50 °C / 95% relative Humidity non condensing				
Frequency programmability	From software, with 10 kHz steps				
Frequency stability	WT from -10°C to 50°C	±1 ppm			
Modulation capability	150 kHz Stereo, 180 kHz Mono/MPX				
Pre-emphasis mode	0 µS, 50 µS (CCIR), 75 µS (FCC)				
POWER REQUIREMENTS					
AC Power Input	AC Supply Voltage	80 ÷ 260 VAC Full Range	115 / 230 ±15% (Internal switch)		80 ÷ 260 VAC Full Range
	Active Power Consumption	70 W	100 W	212 W	260 W
	Overall Efficiency	42 %	50 %	47 %	57 %
	Connector	VDE IEC Standard			
MECHANICAL DIMENSIONS					
Physical Dimensions	L x H x W	483 mm x 88 mm x 394 mm			
Weight	about 7 kg	about 8,5 kg		about 9 kg	
Cooling	Forced, with internal fan				
Acoustic Noise	< 58 dBA			< 75 dBA	
AUDIO INPUTS					
Left/Mono & Right MPX	10 kOhm or 6000ohm (XLR F) Level:-13 to +13 dBu				
SCA/RDS	10 kOhm or 50 Ohm (BNC) Level: -13 to +13 dBu @ 75 KHz FM				
AES/EBU (OPTIONAL)	10 kOhm (2x BNC) Level: -8 to +13 dBu @ 75 KHz FM				
TOSLINK (OPTIONAL)	110 Ohm (XLR F) TOSLINK F05 - EIAJ				
OUTPUTS					
RF Output	50 Ohm (N type)				
RF Monitor	50 Ohm (BNC) approx. -30 dBc		50 Ohm (BNC) approx. -60 dBc		
Pilot output	>5 kOhm (BNC) approx.1Vpp				
FUSES					
On Mains	1 External fuse F 3,15 T - 5x20 mm		1 External fuse F 6,3 T - 5x20 mm		1 External fuse F 8L - 5x20 mm

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice. These are general specifications. They show typical values and are subject to change without notice.

CE 99/5/CE Revision: 08/14

Ordering Information

Code -Codice	Description - Descrizione
Options for TEX-LCD – Opzioni per TEX-LCD	
/AUDIGIN-TEX	AES/EBU audio input option for TEX LCD Series. <i>Opzione ingresso audio AES/EBU per famiglia TEX LCD.</i>
/CW	Morse-coded station ID code generated through FSK (Frequency Shift Keying) function. * <i>Codice identificativo della radio via codice Morse attraverso la funzione FSK(Frequency Shift Keying). *</i>
/RDS-TEX2HE	Built-in RDS system with standard basic functions. <i>Sistema RDS integrato con funzioni base standard.</i>
/TLC-TEX2HE	Internal telemetry system without modem. <i>Sistema di telemetria interna senza modem.</i>
/TLM-TEX2HE	Telemetry system via internal GSM modem. Battery and battery charger included. <i>Sistema di telemetria attraverso modem GSM interno. Batteria e caricabatterie incluso.</i>
/TLW-E-TEX2HE	Basic telemetry system via the Internet. <i>Sistema di telemetria di base attraverso internet.</i>
/TLW-TEX2HE	Telemetry system via the Internet. Battery and battery charger included. <i>Sistema di telemetria attraverso internet. Batteria e caricabatterie include.</i>